

Product Data Sheet

SORB[®]XT 15L Bag

Article	SORB [®] XT 15L Bag
Article No.	100103
Dimensions (mm)	590x300x100
Weight	2,30 kg
Absorption capacity	approx. 4,00 l per kg



Product Information:

Recommended use

- area conservation

Application

- spread out SORB[®]XT evenly over the leaked substance
- work into the material (use mechanical tool, such as a broom, a shovel, Peko XT PLUS by SORB[®] or a dredge)
- fields of application: plants, companies, environment protection, traffic, municipals, on water/streets/asphalt, usual grounds, industrial grounds, special grounds

After application

- skim off or sweep up the substance from the surface
- dispose of the contaminated material following the respective valid laws and local regulations

Storage

- store in resealable container or bag
- store in an dry place with low humidity to avoid mold

Properties

- Multi-absorbent, grain size 0.125 - 4.0 mm, 100% organic, floatable binder, type I, II, III-R, SF
- hydrophobic/oleophilic, bulk density approx. 175 g/l, acts within seconds, highly efficient
- harmless to humans, animals and the environment
- for scattering and absorbing hazardous substances
- absorbs substances such as oil or oil-like substances, fuels, a large number of acids, lubricants, paints, non-stabilised emulsions, brake fluids, coolants, antifreeze, aerosols, alkalis